

Features:

- Isolated mounting base 3000V~
- Pressure contact technology with
Increased power cycling capability
- Space and weight savings

Typical Applications

- AC/DC Motor drives
- Various rectifiers
- DC supply for PWM inverter

$I_{F(AV)}$ **400A**
 V_{RRM} **1900~2500V**
 I_{FSM} **13 A×10³**
 I^2t **845A² S×10³**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Single side water cooled, T _c =60°C	150			400	A
I _{F(RMS)}	RMS forward current		150			628	A
V _{RRM}	Repetitive peak reverse voltage	V _{RRM} tp=10ms V _{RSM} = V _{RRM} +100V	150	1900		2500	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			30	mA
I _{FSM}	Surge forward current	10ms half sine wave	150			13.0	KA
I ² t	I ² T for fusing coordination	V _R =0.6V _{RRM}					845
V _{FO}	Threshold voltage		150			0.85	V
r _F	Forward slop resistance						0.69
V _{FM}	Peak forward voltage	I _{FM} =1200A	25			1.88	V
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine: Single side cooled				0.140	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink	Single side cooled				0.04	°C /W
V _{iso}	Isolation voltage	50Hz, R.M.S, t=1min, I _{iso} : 1mA(max)		3000			V
F _m	Terminal connection torque(M8)				12		N·m
	Mounting torque(M6)				6		N·m
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				1300		g
Outline	405F3/423F3						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7





Fig.8

Outline:



405F3

