

Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers

$I_{F(AV)}$	560 A
V_{RRM}	1100~2000 V
I_{FSM}	5 kA
I^2t	125 10³A²S



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _j (°C)	VALUE			UNIT
					Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Double side cooled,	T _c =85°C	175			560	A
V_{RRM}	Repetitive peak reverse voltage	tp=10ms		175	1100		2000	V
I_{RRM}	Repetitive peak current	at V _{RRM}		175			16	mA
I_{FSM}	Surge forward current	10ms half sine wave		175			5	kA
I^2t	I ² t for fusing coordination	V _R =0.6V _{RRM}					125	A ² s*10 ³
V_{FO}	Threshold voltage			175			0.8	V
r_F	Forward slope resistance						0.86	mΩ
V_{FM}	Peak forward voltage	I _{FM} =600A, F=5kN		25			1.80	V
Q_{rr}	Recovery charge	I _{FM} =1000A, tp=2000μs, di/dt=-20A/μs, V _R =50V		175		1400		μC
$R_{th(j-c)}$	Thermal resistance Junction to case	At 180° sine double side cooled					0.080	°C /W
$R_{th(c-h)}$	Thermal resistance case to heat sink	Clamping force 5.0kN					0.020	
F_m	Mounting force				3.3		5.5	kN
T_{stg}	Stored temperature				-40		175	°C
W_t	Weight					60		g
Outline	ZT19aT							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8

Outline:

