

**Features:**

- Isolated mounting base 3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

Typical Applications:

- Various rectifiers
- DC supply for PWM inverter

V _{RRM}	Type & Outline		
	MDx800-06-410F3	MDx800-08-410F3	MDx800-10-410F3
600V	MDx800-06-410F3	MDx800-08-410F3	MDx800-10-410F3
800V	MDx800-08-410F3	MDx800-10-410F3	MDx800-12-410F3
1000V	MDx800-10-410F3	MDx800-12-410F3	MDx800-14-410F3
1200V	MDx800-12-410F3	MDx800-14-410F3	MDx800-16-410F3
1400V	MDx800-14-410F3	MDx800-16-410F3	MDx800-18-410F3
1600V	MDx800-16-410F3	MDx800-18-410F3	MD800-18-410F3G
1800V	MDx800-18-410F3		
1800V			

MDx stands for any type of **MDC**, **MDA**, **MDK**

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _J (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Single side cooled, T _C =100°C	150			800	A
I _{F(RMS)}	RMS forward current					1256	A
I _{RRM}	Repetitive peak current	at V _{RRM}	150			45	mA
I _{FSM}	Surge forward current	V _R =60%V _{RRM} , t=10ms half sine	150			22.0	kA
I ² t	I ² t for fusing coordination					2420	10 ³ A ² s
V _{FO}	Threshold voltage		150			0.80	V
r _F	Forward slope resistance					0.18	mΩ
V _{FM}	Peak forward voltage	I _{FM} =2400A	25			1.60	V
R _{th(j-c)}	Thermal resistance Junction to case	Single side cooled per chip				0.050	°C/W
R _{th(c-h)}	Thermal resistance case to heatsink	Single side cooled per chip				0.020	°C/W
V _{iso}	Isolation voltage	50Hz,R.M.S,t=1min,I _{iso} :1mA(MAX)		3000			V
F _m	Terminal connection torque(M12)			12		16	N·m
	Mounting torque(M8)			10		12	N·m
T _{vj}	Junction temperature			-40		150	°C
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				3310		g
Outline		410F3					




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7





Fig.8

Outline:

Unmarked dimensional tolerance: ±0.5mm

TECHSEM reserves the right to change specifications without notice.

